

# TEFZEL® 750 ETFE

200° C 300/600Volts

## Ratings/Approvals

300 Volts - UL Style 10109 / CSA AWM I A/B FT1

600 Volts - UL Style 10086 / CSA AWM I A/B FT1

## Construction

Stranded tin or silver plated copper conductor

Extruded Modified Ethylene Tetrafluoroethylene (ETFE)

Standard color coding available

\*600 Volt reduced wall thickness for UL 10412 where not subject to mechanical abuse.

\*150° C available in other stranding for more flexibility: UL 10109, 10086 and 10412

300 Volt		
AWG (Stranding)	OD	Weight/mft
24(7)	.036"	2
22(7)	.041"	3
20(7)	.050"	4
18(7)	.058"	6
16(7)	.074"	10
14(7)	.087"	14
12(19)	.108"	23

600 Volt		
AWG (Stranding)	OD	Weight/mft
24(7)	.044"	2
22(7)	.049"	3
20(7)	.058"	5
18(7)	.066"	6
16(7)	.078"	10
14(7)	.091"	15
12(19)	.118"	24
10(19)	.143"	37
8(19)	.191"	62
6(19)	.231"	94

Consult factory for alternate conductor and stranding options.

\*Tefzel® is a registered trademark of E.I. DuPont de Nemours