

Braidless Silicone Rubber

200° C 600 Volts

Ratings/Approvals

UL Style 3135, 3268, 3530

Construction

Stranded tin plated copper conductor (18awg and larger), nickel plated copper (24-20awg)

Extruded Silicone Rubber

Standard color coding - available in solid colors or stripes

*300 Volts 26-18awg: UL3367

AWG (Stranding)	OD	Weight/mft	UL Style	CSA
24 (7)	.084"	4	3135/3530	AWM IA FT2
22 (7)	.090"	6	3135/3530	AWM IA FT2
20 (7)	.098"	7	3135/3530	AWM IA FT2
18 (7)	.106"	10	3135/3530/3268	AWM IA FT2
16 (7)	.118"	13	3135/3530/3268	AWM IA FT2
14 (7)	.131"	18	3135/3530/3268	AWM IA FT2
12 (19)	.148"	27	3135/3530/3268	AWM IA FT2
10 (19)	.203"	46	3530	AWM IA/B FT2
8 (19)	.261"	73	3530	AWM IA/B FT2
6 (19)	.301"	108	3530	AWM IA/B FT2
4 (133)	.381"	167	3530	AWM IA/B FT2
2 (259)	.449"	260	3530	AWM IA/B FT2
1 (259)	.532"	333	3530	AWM IA/B FT2
1/0 (259)	.570"	415	3530	AWM IA/B FT2
2/0 (259)	.625"	494	3530	AWM IA/B FT2
3/0 (259)	.675"	626	3530	AWM IA/B FT2
4/0 (259)	.746"	759	3530	AWM IA/B FT2

Consult factory for alternate conductor and stranding options.