

Ratings/Approvals

300 Volts - UL Style 1332/CSA 150°C AWM I A/B FT1

600 Volts - UL Style 1330/CSA 180°C AWM I A/B FT1

Construction

Stranded tin or nickel plated copper conductor

Extruded Flourinated Ethylene Propylene (FEP)

Standard color coding available

150°C construction with flexible stranded conductor

(UL Styles 1331 and 1333 are available - consult factory)

300 Volt		
AWG (Stranding)	OD	Weight/mft
24(7)	.054"	3
22(7)	.059"	4
20(7)	.068"	6
18(7)	.076"	8
16(7)	.088"	11
14(7)	.101"	17
12(19)	.118"	25
10(19)	.143"	38

600 Volt		
AWG (Stranding)	OD	Weight/mft
24(7)	.064"	4
22(7)	.069"	5
20(7)	.076"	6
18(7)	.086"	9
16(7)	.098"	13
14(7)	.111"	18
12(19)	.128"	27
10(19)	.153"	40
8(19)	.201"	66
6(19)	.241"	100
4(133)	.321"	156
2(133)	.395"	237
1(259)	.462"	319
1/0(259)	.500"	340
2/0(259)	.555"	477
3/0(259)	.605"	607
4/0(259)	.676"	736

Consult factory for alternate conductor and stranding options.